



PT. SUMBER WISESA INDOLESTARI **INDUSTRIAL COATING & CHEMICALS**

Head Office : Jl. Raya Mauk KM. 7 kawasan Industry Karet Jaya Blok Karet Jaya II No. 7 Sepatan – Tangerang
Telp. : (021) 59372418 (Hunting) Fax. : (021) 59372384, E-mail : swi_paint@telkom.net

NC SANDING SEALER

DESCRIPTION :

SWI NC SANDING SEALER is a single component lacquer, based on Nitrocellulose.

It has fast through dry and easy to sanding.

CHARACTERISTIC :

SWI NC SANDING SEALER is fast drying, after spraying 30 - 45 minutes can be sanded.

It's very easy to sanding, it gives smooth surface. Since the coating film is transparent, it can not influence the color of the wood.

APPLICATION :

SWI NC SANDING SEALER is suitable for using as sealer and filler timber for over coating with Nitrocellulose finishing coats. It is use for polishing furniture and timber paneling.

SPECIFICATION :

Type : One Component Nitrocellulose

Mixing Ratio : Nc Sanding Sealer : Thinner = 1 : 1 = 13 – 14''NK₂



PT. SUMBER WISESA INDOLESTARI **INDUSTRIAL COATING & CHEMICALS**

Head Office : Jl. Raya Mauk KM. 7 kawasan Industry Karet Jaya Blok Karet Jaya II No. 7 Sepatan – Tangerang
Telp. : (021) 59372418 (Hunting) Fax. : (021) 59372384, E-mail : swi_paint@telkom.net

Appearance	: Milky Transparent
Solid Content by Weight	: 40% - 42%
Viscosity (NK 2 CUP) : 180 – 190''NK ₂	
Specific Gravity	: 0,97 gr/cc
Dry To Touch	: 5 – 10 Minutes
Sanding Ability	: 30 – 45 Minutes
Hard Dry	: 4 Hours
Packing Dry	: 7 – 8 Hours